

AMENDMENTS TO THE CLAIMS:

Complete Listing of Claims

Claims 1-4. (canceled)

Claim 5. (currently amended) An automated emergency alert system, comprising:

a handheld portable communication device operable to initiate communication over a wireless telecommunications network, and comprising a location receiver operable to determine a location of the handheld portable communication device;

a dynamic sensor operable to generate an acceleration profile for the handheld portable communication device;

a memory operable to store one or more predefined acceleration profiles, each predefined acceleration profile associated with an emergency event; one or more processors collectively operable to:

receive from the dynamic sensor an acceleration profile for the handheld portable communication device, the acceleration profile comprising a plurality of discretely sampled acceleration values taken at predetermined time intervals;

access one or more predefined acceleration profiles stored in the memory;

compare the acceleration profile received from the dynamic sensor to the one or more predefined acceleration profiles stored in the memory to determine if the acceleration profile substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles; and

if it is determined that the acceleration profile received from the dynamic sensor substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles stored in the memory, initiate a communication using the wireless telecommunications network to one or more emergency call centers to notify the emergency call center that the emergency event has

occurred The system of Claim 3, wherein the one or more processors are operable to:

determine a velocity of the handheld portable communication device using the location receiver; and

in addition to determining whether the acceleration profile received from the dynamic sensor substantially matches a predefined acceleration profile stored in the memory, use the determined velocity to determine whether an emergency event has occurred.

Claim 6. (currently amended) An automated emergency alert system, comprising:

a handheld portable communication device operable to initiate communication over a wireless telecommunications network, and comprising a location receiver operable to determine a location of the handheld portable communication device;

a dynamic sensor operable to generate an acceleration profile for the handheld portable communication device;

a memory operable to store one or more predefined acceleration profiles, each predefined acceleration profile associated with an emergency event;

one or more processors collectively operable to:

receive from the dynamic sensor an acceleration profile for the handheld portable communication device, the acceleration profile comprising a plurality of discretely sampled acceleration values taken at predetermined time intervals;

access one or more predefined acceleration profiles stored in the memory;

compare the acceleration profile received from the dynamic sensor to the one or more predefined acceleration profiles stored in the memory to determine if the acceleration profile substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles; and

if it is determined that the acceleration profile received from the dynamic sensor substantially matches a predefined acceleration profile in the one or more

predefined acceleration profiles stored in the memory, initiate a communication using the wireless telecommunications network to one or more emergency call centers to notify the emergency call center that the emergency event has occurred The system of Claim 3, wherein the one or more processors are further operable to communicate location information identifying the location of the handheld portable communication device to the one or more emergency call centers if it is determined that the acceleration profile received from the dynamic sensor substantially matches a predefined acceleration profile stored in the memory.

Claim 7. (currently amended) An automated emergency alert system, comprising:

a handheld portable communication device operable to initiate communication over a wireless telecommunications network;

a dynamic sensor operable to generate an acceleration profile for the handheld portable communication device;

a memory operable to store one or more predefined acceleration profiles, each predefined acceleration profile associated with an emergency event;

one or more processors collectively operable to:

receive from the dynamic sensor an acceleration profile for the handheld portable communication device, the acceleration profile comprising a plurality of discretely sampled acceleration values taken at predetermined time intervals;

access one or more predefined acceleration profiles stored in the memory;

compare the acceleration profile received from the dynamic sensor to the one or more predefined acceleration profiles stored in the memory to determine if the acceleration profile substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles; and

if it is determined that the acceleration profile received from the dynamic sensor substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles stored in the memory, initiate a communication

using the wireless telecommunications network to one or more emergency call centers to notify the emergency call center that the emergency event has occurred ~~The system of Claim 1,~~

wherein one or more components in the wireless communication network are operable to determine a location of the handheld portable communication device in compliance with an enhanced 911 (E911) mandate and to communicate this location to the emergency call center.

Claim 8. (currently amended) An automated emergency alert system, comprising:

a handheld portable communication device operable to initiate communication over a wireless telecommunications network;

a dynamic sensor operable to generate an acceleration profile for the handheld portable communication device;

a memory operable to store one or more predefined acceleration profiles, each predefined acceleration profile associated with an emergency event;

one or more processors collectively operable to:

receive from the dynamic sensor an acceleration profile for the handheld portable communication device, the acceleration profile comprising a plurality of discretely sampled acceleration values taken at predetermined time intervals;

access one or more predefined acceleration profiles stored in the memory;

compare the acceleration profile received from the dynamic sensor to the one or more predefined acceleration profiles stored in the memory to determine if the acceleration profile substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles; and

if it is determined that the acceleration profile received from the dynamic sensor substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles stored in the memory, initiate a communication using the wireless telecommunications network to one or more emergency call centers to notify the emergency call center that the emergency event has occurred The system of Claim 1,
wherein:

the memory is further operable to store one or more prerecorded emergency event messages, each event message associated with one or more emergency events; and

the one or more processors are further operable to communicate a prerecorded event message to the emergency call center when a substantial match is determined.

Claim 9. (currently amended) An automated emergency alert system, comprising:

a handheld portable communication device operable to initiate communication over a wireless telecommunications network;

a dynamic sensor operable to generate an acceleration profile for the handheld portable communication device;

a memory operable to store one or more predefined acceleration profiles, each predefined acceleration profile associated with an emergency event;

one or more processors collectively operable to:

receive from the dynamic sensor an acceleration profile for the handheld portable communication device, the acceleration profile comprising a plurality of discretely sampled acceleration values taken at predetermined time intervals;

access one or more predefined acceleration profiles stored in the memory;

compare the acceleration profile received from the dynamic sensor to the one or more predefined acceleration profiles stored in the memory to

determine if the acceleration profile substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles; and
if it is determined that the acceleration profile received from the dynamic sensor substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles stored in the memory, initiate a communication using the wireless telecommunications network to one or more emergency call centers to notify the emergency call center that the emergency event has occurred The system of Claim 1,
wherein:

the memory is further operable to store prerecorded user information regarding a user associated with the handheld portable communication device;
and

the one or more processors are further operable to communicate the prerecorded user information regarding the user to the emergency call center when a substantial match is determined.

Claim 10. (currently amended) An automated emergency alert system, comprising:

a handheld portable communication device operable to initiate communication over a wireless telecommunications network;

a dynamic sensor operable to generate an acceleration profile for the handheld portable communication device;

a memory operable to store one or more predefined acceleration profiles, each predefined acceleration profile associated with an emergency event;

one or more processors collectively operable to:

receive from the dynamic sensor an acceleration profile for the handheld portable communication device, the acceleration profile comprising a plurality of discretely sampled acceleration values taken at predetermined time intervals;

access one or more predefined acceleration profiles stored in the memory;

compare the acceleration profile received from the dynamic sensor to the one or more predefined acceleration profiles stored in the memory to determine if the acceleration profile substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles; and
if it is determined that the acceleration profile received from the dynamic sensor substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles stored in the memory, initiate a communication using the wireless telecommunications network to one or more emergency call centers to notify the emergency call center that the emergency event has occurred The system of Claim 4,

further comprising a temperature sensor operable to monitor a temperature near the handheld portable communication device, the one or more processors further operable to:

receive from the temperature sensor temperature information regarding the temperature near the handheld portable communication device; and

if the information received indicates that the temperature near the handheld portable communication device exceeds a predefined threshold temperature, communicate a message regarding the temperature to the one or more emergency call centers.

Claim 11. (currently amended) An automated emergency alert system, comprising:

a handheld portable communication device operable to initiate communication over a wireless telecommunications network;

a dynamic sensor operable to generate an acceleration profile for the handheld portable communication device;

a memory operable to store one or more predefined acceleration profiles, each predefined acceleration profile associated with an emergency event;
one or more processors collectively operable to:

receive from the dynamic sensor an acceleration profile for the handheld portable communication device, the acceleration profile comprising a plurality of discretely sampled acceleration values taken at predetermined time intervals;

access one or more predefined acceleration profiles stored in the memory;

compare the acceleration profile received from the dynamic sensor to the one or more predefined acceleration profiles stored in the memory to determine if the acceleration profile substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles; and

if it is determined that the acceleration profile received from the dynamic sensor substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles stored in the memory, initiate a communication using the wireless telecommunications network to one or more emergency call centers to notify the emergency call center that the emergency event has occurred The system of Claim 1,

further comprising a water sensor operable to monitor whether the handheld portable communication device is under water, the one or more processors further operable to:

receive from the water sensor information regarding whether the handheld portable communication device is under water; and

if the information received indicates that the handheld portable communication device is under water, communicate a message indicating that the handheld portable communication device is under water to one or more emergency call centers.

Claims 12-14. (canceled)

Claim 15. (currently amended) A method for automated emergency alert using a handheld portable communications device operable to initiate communication over a wireless telecommunications network, comprising:

determining a location of the handheld portable communication device using a global positioning system (GPS) receiver associated with the handheld portable communication device;

storing one or more predefined acceleration profiles, the acceleration profile comprising a plurality of discretely sampled acceleration values taken at predetermined time intervals, each predefined acceleration profile associated with an emergency event;

receiving an acceleration profile for the handheld portable communication device;

accessing one or more of the stored predefined acceleration profiles;

comparing the acceleration profile to the one or more stored predefined acceleration profiles to determine if the acceleration profile substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles; and

if it is determined that the acceleration profile substantially matches a stored predefined acceleration profile in the one or more predefined acceleration profiles, initiating a communication using the wireless telecommunications network to one or more emergency call centers to notify the emergency call center that the emergency event has occurred The method of Claim 14, further comprising:

determining a velocity of the handheld portable communication device using a location receiver; and

in addition to determining whether the acceleration profile received from the dynamic sensor substantially matches a predefined acceleration profile stored in the memory, using the determined velocity to determine whether an emergency event has occurred.

Claim 16. (currently amended) A method for automated emergency alert using a handheld portable communications device operable to initiate communication over a wireless telecommunications network, comprising:

determining a location of the handheld portable communication device using a global positioning system (GPS) receiver associated with the handheld portable communication device;

storing one or more predefined acceleration profiles, the acceleration profile comprising a plurality of discretely sampled acceleration values taken at predetermined time intervals, each predefined acceleration profile associated with an emergency event;

receiving an acceleration profile for the handheld portable communication device;

accessing one or more of the stored predefined acceleration profiles;

comparing the acceleration profile to the one or more stored predefined acceleration profiles to determine if the acceleration profile substantially matches a predefined acceleration profile in the one or more predefined acceleration profiles; and

if it is determined that the acceleration profile substantially matches a stored predefined acceleration profile in the one or more predefined acceleration profiles, initiating a communication using the wireless telecommunications network to one or more emergency call centers to notify the emergency call center that the emergency event has occurred The method of Claim 14, further comprising communicating location information identifying the location of the handheld portable communication device to the one or more emergency call centers if it is determined that the acceleration profile substantially matches a predefined acceleration profile.

Claims 17-20. (canceled)